



AT-8000S/24POE

Layer 2 Stackable Fast Ethernet Switch

AT-8000S/24POE

24-port stackable 10/100TX Power over Ethernet switch with 2 active SFP bays (unpopulated) and 2 standby 10/100/1000T ports (RJ-45)

Overview

One of a series of stackable switches from Allied Telesis, the AT-8000S/24POE provides high performance Layer 2 switching in an affordable fixed configuration platform combined with Power over Ethernet to provide power to edge devices including IP Phones and wireless access points. This switch offers 24 10/100 ports, two fixed SFP Combo slots plus two integrated stacking connectors that deliver a total of 4Gbps stacking bandwidth. The stacking capability integrated into this platform is configured as a resilient ring topology designed to provide high reliability and simplified management for higher port density applications.

Combined Ethernet and Power for Branch Office and Wiring Closet Connectivity

Powerful line rate performance and stackability make this switch ideal for branch offices or the wiring closet of larger offices where power is needed for remote devices. The state-of-the-art QoS capability of this product ensures reliable delivery of advanced network services such as voice while effectively controlling the continually increasing traffic needs found in today's networks.

Easy Access Networking

Featuring an industry standard CLI and Allied Telesis' intuitive yet fully featured WEB interface the advanced features of the AT-8000S/24POE are accessible to a wide range of system administrators. The well known CLI and WEB interfaces significantly reduce learning time and minimize the cost of deployment.

Secure Management

Only authorized administrators can access the management interface of the AT-8000S series. Protocols such as SSL, SSH and SNMP v3 facilitate this protection of your network with local or remote connections.

Securing the Network Edge

To ensure the protection of your data, it is important to control access to your network. Protocols such as 802.1x port based authentication guarantee that only known users are connected to the network. Unknown users who physically connect can be isolated to a pre-determined part of your network offering guests such benefits as Internet access while ensuring the integrity of your private network data.

Gigabit and Fast Ethernet SFP Support

All switches in the 8000S family support both gigabit and Fast Ethernet Small Form-factor Pluggables (SFPs). This makes the 8000S series an ideal family for environments where gigabit fiber switches will be phased in over time. The 8000S family allows for connectivity to the legacy 100FX hardware until it is upgraded to gigabit. Support for both speeds of SFPs allows organizations to stay within budget as they migrate to faster technologies.

Key Features

Easy, Well Known Management

- Industry Standard CLI
- Simple intuitive, fully featured Allied Telesis Web Interface
- Secure encrypted WEB and CLI management with SSH v2 and SSL
- SNMP

Power over Ethernet

- Provides standards based 802.3af Power over Ethernet to all 24 10/100 ports
- Support for up to 24 class 2 Powered devices at 7.3 watts
- Support for up to 12 class 3 Powered devices at 15.4 watts

Affordable Truly Stackable 10/100 Switching Platform

- Single IP address Stack management
- 4Gig Resilient Ring Stacking Architecture
- Across Stack Link Aggregation
- Across Stack VLAN configuration
- Across Stack Port Mirroring
- Redundant standby stack master

All the QoS needed in the wiring closet for today's Voice and Data Networking

- 8 Priorities assigned to 4 queues
- 802.1p for Layer 2 QoS
- DSCP (Diffserv) for Layer 3 QoS
- 802.1p to DSCP remarking traffic ready for transport to the Layer 3 core of the network

Securing the Network at its most vulnerable point

- 802.1x and RADIUS network login: *for advanced control of user authentication and accountability*
- Guest VLAN: *to ensure visitors or unauthorized users connect only to services defined by IT. E.g. Internet*
- TACACS+: *for ease of management security administration*

AT-8000S/24POE | Layer 2 Stackable Fast Ethernet Switch

System Configuration

W x D x H	440mm x 257mm x 44mm (17.32" x 10.11" x 1.76")
Weight	3.7kg
Mounting	19" rack-mountable hardware included

System Capacity

64MB RAM
16MB Flash Memory
400Mhz CPU
Up to 4,096 VLAN ID
8,000 MAC address

Performance

Wire speed switching on all Ethernet ports
14,880pps for 10Mbps Ethernet
148,800pps for 100Mbps fast Ethernet
1,448,000pps for 1000Mbps Gigabit Ethernet

Ethernet throughput	4.4Gbps
Chipset switching capacity	12.8Gbps
MTBF	252,271.22 hours
Store and forward mode	
Non blocking switch fabric	
Auto-MDI/MDI-X	

Port speed	
10/100-TX	RJ-45
10/100/1000TX	RJ-45
100-FX, 1000-SX, 1000-LX	SFP slot
RS232	DB9 pin, male port
Internal power supply	

Power over Ethernet

Total Power Budget	225W
For Switch	12V/ 45W
POE Budget	50V/ 180W
POE Max supported 802.3af class 3 devices (15.4W):	
11 ports	
POE Max supported 802.3af class 2 devices (7.3W):	
24 ports	

Interface Standards

802.3	10Base-T & 10Base-FL
802.3u	100Base-TX & 100base-FX
802.3z	1000base-SX
802.3ab	1000Base-T

General Standards

802.1d	Bridging
802.3x	BackPressure/ Flow Control

Redundancy Standards

802.1D	Spanning Tree Protocol
802.1W	Rapid Spanning Tree
802.1s	Multiple Spanning Tree
802.3ad	LACP Link Aggregation (with up to eight members per group and up to eight groups per device)

Static port trunk

Quality of Services (QoS)

QoS in layer 2 (802.1p compliant Class of Service)
Traffic prioritization using 802.1p, ToS, DSCP fields
Map 802.1p priorities to CoS queues to prioritize traffic at Egress.
Strict Scheduling and Weighted Round Robin

VLANs

IEEE 802.1Q VLAN Tagging
Up to 256 VLANs
Port-based VLANs
MAC-based VLANs
Private VLANs
GARP VLAN Registration Protocol (GVRP)

Multicast Standards

RFC 1112	IGMP snooping (ver. 1)
RFC 2236	IGMP snooping (ver. 2)
RFC 3376	IGMP snooping (ver. 3)*

*Future release

Management and Monitoring

WEB, CLI, Serial	
RFC 1157	SNMPv1/v2c
RFC 2570	SNMPv3
RFC 1213	MIB-II
RFC 1573	Evolution of MIB-II
RFC 1215	TRAP MIB
RFC 1493	Bridge MIB
RFC 2863	Interfaces group MIB
RFC 1643	Ethernet like MIB
RFC 1757	RMON 4 groups: Stats, History, Alarms, Events
RFC 2674	802.1Q MIB
RFC 1866	HTML
RFC 2068	HTTP
RFC 854	Telnet
RFC 783	TFTP

IP address allocation
RFC 951/ RFC 1542 BootP/ DHCP Manual

RFC 2030 SNMP, Simple Network Time Protocol
Syslog Event
Dual Software Images

Stacking
Up to six units
Single chip appearance
Single IP management
Backup master
Full duplex link with 2Gbps performance
Trunking across stack
Port mirroring across stack
VLAN across stack

Security

Management Security: user name and password protection
SSHv2 Telnet management
SSLv3 WEB management
RFC 1492 TACACS+
RFC 2138 RADIUS Authentication
IEEE 802.1x Port-based network access control
Guest VLANs

Fault Protection

Broadcast Storm Control

AT-8000S/24POE | Layer 2 Stackable Fast Ethernet Switch

Power Characteristics

Voltage Input	100-240VAC
Voltage Output	48VDC
Current	1.5A
Heat Dissipation	768.3 BTU/hour
Clock Frequency	166Mhz

Environmental Specifications

Operating Temp	0°C to 45°C (32°F to 113°F)
Storage Temp	-25°C to 70°C (-13°F to 158°F)
Relative Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Operating Altitude	maximum 3,000m (9,843ft)

Electrical/ Mechanical Approvals

Safety	UL 1950 (UL/cUL), EN60950 (TUV)
EMI	FCC Class A, EN55022 Class A, VCCI Class A, C-Tick, EN61000-3-2, EN61000-3-3
Immunity	EN55024
RoHS	compliant

Package Description

One AT-8000S/24POE switch
Power cord AC
Rackmount kit
Rubber feet for desktop installation
RS232 management cable
Stacking cable
User guide in CD

Country of Origin

China

Ordering Information

AT-8000/24POE-xx

24-port stackable 10/100TX POE L2 switch with 2 active SFP bays (unpopulated) and 2 standby 10/100/1000T ports (RJ-45)

Where xx = 10 for US Power cord
20 for no power cord
30 for UK power cord
40 for Australian power cord
50 for European power cord

Accessories

Small Form Pluggables (SFPs)

AT-SPFX/2

Multi-mode Fiber, GbE Small Form-factor Pluggable (SFP)

AT-SPFX/15

Single-mode Fiber, GbE Small Form-factor Pluggable (SFP)

AT-SPFX/40

Single-mode Fiber, GbE Small Form-factor Pluggable (SFP)

AT-SPTX

Copper, GbE Small Form-factor Pluggable (SFP)

AT-SPSX

Multi-mode Fiber, GbE Small Form-factor Pluggable (SFP)
850nm

AT-SPLX10

Single-mode Fiber, 10km, GbE SFP, 1310nm

AT-SPLX40

Single-mode Fiber, 40km, GbE SFP, 1310nm

AT-SPLX40/1550

Single-mode Fiber, 40km, GbE SFP, 1550nm

AT-SPZX80

Single-mode Fiber, 80km, GbE SFP, 1550nm

AT-SPZX80/xxxx

Single-mode Fiber, CWDM, 80km GbE SFP

CWDM Wavelengths:

Where xxxx = 1470
1490
1510
1530
1550
1570
1590
1610

USA Headquarters | 19800 North Creek Parkway | Suite 200 | Bothell | WA 98011 | USA | T: +1 800 424 4284 | F: +1 425 481 3895

European Headquarters | Via Motta 24 | 6830 Chiasso | Switzerland | T: +41 91 69769.00 | F: +41 91 69769.11

Asia-Pacific Headquarters | 11 Tai Seng Link | Singapore | 534182 | T: +65 6383 3832 | F: +65 6383 3830

www.alliedtelesis.com

© 2006 Allied Telesis Inc. All rights reserved. Information in this document is subject to change without notice. All company names, logos, and product designs that are trademarks or registered trademarks are the property of their respective owners. 617-000180 Rev.D