

A WHOLE NEW ASUS EXPERIENCE

Built on **ASUS**

Z63A Datasheet

| | |
|--------------------------------------|--|
| Processor & Cache Memory | <ul style="list-style-type: none"> -Intel® Pentium® M Processor with 2MB on-die cache - Speeds at 1.6Ghz-2.13Ghz (Dothan), 400 & 533Mhz FSB -Mobile Intel Celeron M Processor with 512K/1MB on Die L2 Cache -Speed from 1.3Ghz-1.7+Ghz |
| Operation System | Microsoft® Windows® XP Professional Edition |
| Chipset | Intel 915GM & ICH6-M |
| Main Memory | DDR2-400/533MHz up to 1024MB 2 x SODIMM Dual Channel Slots |
| Display | 14" WXGA (1280 x 768) TFT display Enhanced Screen |
| Video Graphics & Memory | Embedded Graphic for up to 128MB |
| Hard Drive | 2.5-inch ultra-slim 9.5mm HDD, capacity of 20/40/60/80 GB and 4200 & 5400 RPM |
| Optical Drive | Interchangeable 24X/24X/8X/24X DVD+CD-RW Combo module Interchangeable 8X/24X/24X/10X/8X/4X/8X/4X DVD-RW/DVD+RW Dual module Support Module Hot Swap Function and 2nd HDD/2nd Battery |
| Fax / Modem / LAN / WLAN / Bluetooth | <ul style="list-style-type: none"> - Azalia compliant MDM Fax/ Modem - Integrated MDC Fax/Modem - Modem supported V.90 and universal PPT - On board 10/100/1000 Mbps Fast Ethernet controller, support full and half duplex mode - Support wireless 802.11a/b/g |
| LED Status Indicator | <ul style="list-style-type: none"> - Power-on/Suspend - Battery Charging/full/low - Storage device access - WLAN Connectivity - Caps Lock, Num Lock |
| Interface | <ul style="list-style-type: none"> 3 x USB 2.0 ports 1 x VGA port/Mini D-sub 15-pin for external monitor 1 x IEEE 1394 port 1 x Card Reader 1 x 32-bit PC CardBus 1.0 architecture 2 x Audio jack: Audio out (SPIDIF) / Mic-in 1 x Type II PCMCIA slot 1 x RJ11 connector fro Modem 1 x RJ45 connector for Ethernet 1 x TV-out (S-Video) |
| Keyboard | <ul style="list-style-type: none"> - At least 19mm ergonomic & 2.35mm travel (query key only) 83-key with Win_XP function key |

| | |
|----------------------|---|
| Audio | Built-in Azalia compliant audio chip, with 3D effect & full duplex Built-in speaker and microphone |
| Power Management | Full feature SMI power management, Stand-by, Suspend to Disk, and Suspend to RAM ACPI 1.0b and 2.0 (partially) supported |
| Battery Pack & Life | Li-Ion 8 cell: 4400mAh, 4S2P, 65W/Hrs Built-in gauge IC Battery low-low enters Save-To-Disk mode Run-time: 4+ Hrs |
| AC Adapter | Output: 19 V DC, 3.42 A, 65W Input: 100—240V AC, 50/60Hz universal 3 / 2 pin compact power supply system |
| Dimension & Weight | 13" x 9.7" x 1.18"~1.29" inches (WXDXH) - 4.8lbs |
| Security | BIOS setup, Power-on, HDD User Password Protection, BIOS I/O lock Kensington Lock |
| Supplied Accessories | Carrying bag |
| Warranty & Support | -1 year limited warranty -Upgradeable up to total 3 yrs |